



UG User Guide 1011 How to laminate your print to a TuphMount

Attach the TuphMount backer

Attach the Tuphmount backer to your wall or structure. Make certain that the fixings are not proud of the countersunk holes or the print will be damaged.

Prepare the TuphMount backer for laminating

Remove all fingerprints, dust and dirt from the backer. Assume that the surface is contaminated even if it looks clean. Use methylated spirits on a paper towel. Before the meths evaporates wipe dry with a second paper towel. Replace both paper towels frequently.

Laminate the print to the TuphMount backer

The adhesive liner is pre-slit. Peel liner away until a 30-50mm 'tab' protrudes. Crease the liner. Don't touch the exposed adhesive! Carefully place the print on the backer, the tabs will prevent adhesive contact while positioning.

Gently press the print onto the backer on the **X** Check the other end of the sheet, adjust as required. If you do stuff it up **DO NOT PULL THE SHEET UPWARD** twist it horizontally to remove.

Press the sheet firmly on the **X** pull the tabs alternating from side to side in 50mm increments. Press the centre of the sheet firmly onto the backer as you go down. Press outward from the centre to force out air pockets. Finish by pressing firmly around all the edges.

We're here to help, so please call or email if you get stuck.
Phone Andrew on 0275 577 119, or andrew@metalimage.co.nz

